

Single Stage Pressure Regulators

VSR-610UB Series


VIGOUR

Product Feature

- Single-stage pressure regulator
- 10µin. Ra surface finish (25µin. Ra optional)
- Minimized internal volume for short purge times
- All materials used meet ASTM A479 / A484 / A276 standards
- The product is fabricated in compliance with the VS001B process specification
- Internal connectors for pressure gauges
- High control accuracy
- Metal-to-metal seal to atmosphere
- Simple outlet pressure limitation by hand-wheel
- 100% helium-leak-tested





Dimensions (mm)




Technical Data

Type:	single-stage
Inlet pressure P1:	Max. 3500 psig (250bar)
Outlet pressure P2:	Vac to 10/30/60/100 psig (1/2/4/7bar)
Surface finish:	10µin. Ra (25µin. Ra optional)
Materials	
Body:	see ordering info
Valve seat:	PCTFE (VespeI® optional)
Diaphragm:	Hastelloy® C276
Inlets and Outlets:	1/4" / 3/8" or 1/2" VFS fitting or tube weld
Bonnet port:	1/8" NPT (on panel mount option, bonnet port is not threaded)
Temperature range:	-40°F to +160°F (-40°C to +71°C)
Leak rate: (to atmosphere)	1x10 ⁻⁹ mbar l/s He
(via seat)	1x10 ⁻⁸ mbar l/s He
Flow capacity:	Cv=0.13
Supply pressure effect:	0.25 psig rise in delivery pressure per 100 psig source pressure drop
Weight:	approx. 1.54kg (depending on connections or options)

Flowchart



Ordering Information



Inlet/outlet Connection

FV4: 1/4" VFS female

MV4: 1/4" VFS male

FV6: 3/8" VFS female

MV6: 3/8" VFS male

FV8: 1/2" VFS female

MV8: 1/2" VFS male

IFV4: 1/4" (gauge female threaded connection
machined on the body)

TW4: 1/4" tube weld


TW6: 3/8" tube weld

TW8: 1/2" tube weld

P: gauge (1/4" VFS fitting)

IP: gauge (IFV4 fitting)

* Other connection standard, consult factory



Ordering Example

VSR - 610UBS - 250 - V4 - 2P - MV4 - FV4

1 - 2

